


# CONNECT

## The optimum connection

CONNECT plastic enclosures are ideal for wired applications.

- two enclosure shells, convex and flattened with a recessed panel
- the two shells snap into each other, no screws required, this saves time during assembly, and you can also choose the front side of the device
- cutouts at both ends; to complete the enclosure, end parts and/or cable glands can be fitted
- three enclosure lengths
- the enclosure shells and the end parts are made of UV-stabilised V-0 material
- protection class IP 40 (with end parts)
- integrated strain relief with the cable gland kit
- enough room for the installation of compact displays, LEDs and USB connectors
- recessed surface to protect the membrane keyboard, decor foil or label
- attachment pillars for PCBs and components in the flat enclosure shell
- holding clamps for round tubes up to  $\varnothing$  32 mm available as accessories (for enclosure lengths 116 and 156 mm)
- holder for secure storage on the wall or similar as an accessory



# CONNECT

## Applications and Examples

- Data systems engineering
- Network technology
- Building services systems
- Safety engineering
- IoT/ IIoT
- Medical and therapeutic applications
- Measuring and control technology



Receiver and data transfer for EMR



Tool for making colloidal silver solutions



Voltage and current display during trickle charging

## Customising Options

What do you still need for your own very personal product? We can supply enclosures and tuning knobs with all necessary modifications for fitting your electronic components. Customising options for Connect



Machining



Lacquering



Printing



Laser marking



Decor foils



EMC shielding



Installation / Assembly of accessories

# CONNECT

## Select Versions



**B2832107**  
CONNECT  
ASA+PC-FR (UL 94 V-0)  
off-white RAL 9002  
76x54x22mm



**B2832109**  
CONNECT  
ASA+PC-FR (UL 94 V-0)  
black RAL 9005  
76x54x22mm



**B2833107**  
CONNECT  
ASA+PC-FR (UL 94 V-0)  
off-white RAL 9002  
116x54x22mm



**B2833109**  
CONNECT  
ASA+PC-FR (UL 94 V-0)  
black RAL 9005  
116x54x22mm



**B2834107**  
CONNECT  
ASA+PC-FR (UL 94 V-0)  
off-white RAL 9002  
156x54x22mm



**B2834109**  
CONNECT  
ASA+PC-FR (UL 94 V-0)  
black RAL 9005  
156x54x22mm

## Accessory to complete



**B2811207**  
End part  
ASA+PC-FR (UL 94 V-0)  
off-white RAL 9002



**B2811209**  
End part  
ASA+PC-FR (UL 94 V-0)  
black RAL 9005



**B2911308**  
Cable gland kit, 3.4 - 4.2  
SEBS (TPE)  
volcano



**B2911309**  
Cable gland kit, 3.4 - 4.2  
SEBS (TPE)  
black RAL 9005



**B2911318**  
Cable gland kit, 4.2 - 5.0  
SEBS (TPE)  
volcano



**B2911319**  
Cable gland kit, 4.2 - 5.0  
SEBS (TPE)  
black RAL 9005



**B2911328**  
Cable gland kit, 5.0 - 5.9  
SEBS (TPE)  
volcano



**B2911329**  
Cable gland kit, 5.0 - 5.9  
SEBS (TPE)  
black RAL 9005

# CONNECT

## Accessory "wall/holder"



**A9167027**  
Holding clamp  
PA 6 (UL 94 HB)  
off-white RAL 9002



**A9167029**  
Holding clamp  
PA 6 (UL 94 HB)  
black RAL 9005



**B2931507**  
Holder  
ASA+PC-FR (UL 94 V-0)  
off-white RAL 9002



**B2931509**  
Holder  
ASA+PC-FR (UL 94 V-0)  
black RAL 9005

## Accessory "screws"



**A0304031**  
Self-tapping screws 2.2 x 5 mm  
(PZ1)

Subject to technical modification without notice. © by OKW Gehäusesysteme, Buchen/Germany.