

SMART-CONTROL 拐角盒

可安装于角落的机盒

SMART-CONTROL 拐角盒是第一个可在建筑角落方便安装的机盒。此外，其机盒系列也可以安装在墙壁和桌面上，并合适符合人体工程学的倾斜度的使用。

- 2 种规格，M 和 S
- 提供凸面设计式或带有嵌入式面板以保护膜键盘
- 高质材料 ASA 混合 PC 至 FR、具备高度防紫外线特性、标准颜色为灰白色（RAL 9002）
- 机盒背面的固定装置采用 Torx 梅花不锈钢螺钉
- 达到 IP 55 保护等级的垫圈可选（作为附件）
- 特殊壁挂支架（作为附件），用于将机盒安装在 90° 的内壁角或平壁上
- 桌面支架（作为附件）可将机盒稳固地横向放置在桌子上，并合适符合人体工学的读取角度为 45° 的使用
- 在上盒和下盒各具备一电路板安装格



SMART-CONTROL 拐角盒

应用示例

环保技术。IoT/IIoT。出入控制设施。测量和控制技术。自动化技术。医疗和实验室技术。环保技术。



AAL assistance system



Aerosol meter



CARRIER CONTROL



Dementia Protection System



Room air measuring device

按客户要求修改加工

如何体现您的特殊产品？如有需要，我们执行所有必要的修改和精加工，提供组装完毕的机盒。产品类型用于 Smart-Control 拐角盒



机械加工



表面涂渡



图文打印于机盒



激光打印字体



装饰膜



EMC 保护



制备 / 组装

SMART-CONTROL 拐角盒

类型



B4608107
SMART-CONTROL S, Vers. I
ASA+PC (UL 94 V-0)
off-white RAL 9002
142x81x46mm
IP 40, IP 55 opt.



B4608207
SMART-CONTROL S, Vers. II
ASA+PC (UL 94 V-0)
off-white RAL 9002
142x81x46mm
IP 40, IP 55 opt.



B4610107
SMART-CONTROL M, Vers. I
ASA+PC (UL 94 V-0)
off-white RAL 9002
173x101x59mm
IP 40, IP 55 opt.



B4610207
SMART-CONTROL M, Vers. II
ASA+PC (UL 94 V-0)
off-white RAL 9002
173x101x59mm
IP 40, IP 55 opt.

“底座” 配件



B4705207
Desktop stand set
ASA+PC (UL 94 V-0)

“保护等级” 附件



B4708920
Seal S



B4710920
Seal M

“挂墙支架” 配件



B4705907
Wall suspension element
ASA+PC (UL 94 V-0)

SMART-CONTROL 拐角盒

“螺钉” 附件



A0325060
Self-tapping screw 2.5 x 6 mm
(T8)
Stainless steel

保留技术更改可能性。© OKW 机盒系统, Buchen/德国。